

LED FILAMENT ŽARULJA

LFB-3210



HR BA TEHNIČKI LIST

Snaga:	4 W
Tip grla:	E14
Boja svjetlosti:	2700 K
IP stupanj zaštite:	IP20
Napon:	AC 170 - 265 V / 50 - 60 Hz
FLUX:	100 lm / W ~ 400 lm
Kut svjetlosti:	360 °
LED diode:	San`an
Oblik:	C35
PF:	0,9
CRI:	80
Radna temperatura:	-20 °C~65 °C
Mogućnost dimovanja:	Da
Radni vijek:	35 000 radnih sati
Materijal:	amber staklo
Dimenzije/Težina:	35 x 100 mm/0,015 kg



LED ŽARNICA Z ŽARILNO NITKO

LFB-3210



SI PODATKOVNI LIST IZDELKA

Moč:	4 W
Podnožje žarnice:	E14
Barva svetlobe:	2700 K
IP stopnja:	IP20
Napetost:	AC 170 - 265 V / 50 - 60 Hz
FLUX:	100 lm / W ~ 400 lm
Svetlobni kot:	360 °
LED diode:	San`an
Oblika:	C35
PF:	0,9
CRI:	80
Delovna temperatura:	-20 °C~65 °C
Zatamnitev:	Da
Življenska doba:	35 000 obratovalnih ur
Materijal:	jantarno steklo
Dimenzije/Teža:	35 x 100 mm/0,015 kg



DE PRODUKTDATENBLATT

Leistung:	4 W
Glühbirnensockel:	E14
Helle Farbe:	2700 K
IP-Schutzart:	IP20
Spannung:	AC 170 - 265 V / 50 - 60 Hz
FLUX:	100 lm / W ~ 400 lm
Lichtwinke:	360 °
LED Diode:	San`an
Form:	C35
PF:	0,9
CRI:	80
Betriebstemperatur:	-20 °C~65 °C
Dimmbare Funktion:	Ja
Lebensdauer:	35 000 Betriebsstunden
Material:	Braunglas
Maße/Gewicht:	35 x 100 mm/0,015 kg



LED FILAMENT BULB

LFB-3210



EN PRODUCT DATASHEET

Power:	4 W
Bulb base:	E14
Color temperature:	2700 K
IP protection rate:	IP20
Voltage:	AC 170 - 265 V / 50 - 60 Hz
FLUX:	100 lm / W ~ 400 lm
Beam angle:	360 °
LED chip:	San`an
Shape:	C35
PF:	0,9
CRI:	80
Operating temperature:	-20 °C~65 °C
Dimmable:	Yes
Life span:	35 000 working hours
Material:	amber glass
Dimensions/Weight:	35 x 100 mm/0,015 kg

